



- ▶ New and Improved
- Defect Free
- ► Light yet strong & stable
- Wide range of profiles& dimensions
- ► Easily worked cut & drill
- Easily painted priming system ready to top-coat











GREAT FOR: Skirting, Architraves, Jambs, Reveals, Shelving, Joinery, Furniture, Bathrooms and Kitchens (not exposed to constant wetting) and any interior finishing application that requires the great look of timber mouldings.



HALF SPLAY AS4

5.4m
5.4m
5.4m



HALF SPLAY AS5

66 x 18mm	5.4m
90 x 18mm	5.4m



SPLAYED AS8

5.4m 5.4m
5.4m



PENCIL ROUND AS15

66 x 11mm	5.4m
90 x 11mm	5.4m



PENCIL ROUND AS7

66 x 18mm	5.4m
90 x 18mm	5.4m



LAMB'S TONGUE

66 x 18mm	5.4m
90 x 18mm	5.4m

REAL TIMBER FOR REAL BUILDERS

THE TIMBER

EziTrimplus is manufactured from sustainable plantation grown Radiata Pine (Pinus radiata). Which has been milled, kiln dried and docked to remove all knots and visible Imperfections. This is then used to produce a fingerjointed / laminated moulding, or door jamb which has no defects, whilst also having the superior finish that you have come to expect from the EziTrim Brand.

THE GLUE

The glue used in the fingerjointing and laminating process is designed to give EziTrimplus strength and Flexibility. The glue is moisture resistant and will withstand short term exposure to the moisture under typical indoor building conditions, i.e Kitchens and Bathrooms.



BEVEL AS3

42 x 18mm	5.4m
66 x 15/18mm	5.4m
	• · · · · · ·
90 x 18mm	5.4m
138 x 18mm	5.4m



BEVEL ROUND

66 x 18mm	5.4m
90 x 18mm	5.4m



BULLNOSE AS1

42 x 18mm	5.4m
66 x 18mm	5.4m
90 x 18mm	5.4m
138 x 18mm	5.4m



VICTORIAN COLONIAL

5.4m
5.4m
5.4m



STEP AS12

66 x 18mm 5.4m



LINING BOARDS 302 & 321

140 x 12mm 5.4m

THE PRIMER

The Unique feature of EziTrimplus mouldings is the priming process that creates not only good looks but a functional finish. The priming system involves up to three separate applications of different primer formulations which are hand sanded and buffed between coats. These primers create a finish which helps reduce the effects of raised grain and visible finger joints, that is both flexible and tough, with the added advantage of being 'top coat ready'

PAINTING

All nail holes should be filled with an appropriate wood filler, and then sanded back to achieve a smooth surface (in accordance with manufacturers guidelines). All dust and dirt should then be wiped away before coating all bare timber with a wood primer. Once the surface has been prepared, simply apply your preferred top coat in accordance with paint manufacturers recommendations. EziTrimplus mouldings, door Jambs and window reveals can be painted with either acrylic, enamel or latex paints.

DISPOSAL

All timber off cuts should be disposed of in council approved landfill or incineration sites. It is not recommended to burn primed or painted timber in heaters and BBQ, both indoors and outdoors. This product or sawdust and shavings should not be used for Mulch or Animal bedding.



DAR - DRESSED ALL ROUND

30 x 11mm	5.4m
42 x 11mm	5.4m
66 x 11mm	5.4m
90 x 11mm	5.4m
18 x 18mm	5.4m
42 x 18mm	5.4m
66 x 18mm	5.4m
90 x 18mm	5.4m
110 x 18mm	5.4m
138 x 18mm	5.4m
185 x 18mm	5.4m



QUAD	
18 x 18mm	5.4m



TRI QUAD	
18 x 18mm	5.4m







LOOSE JAMB SET

30 x 11mm 2.1m 110 x 18mm 2.1m

