SMARTFRAME® POWERED BY INNOVATION







High Performance

SmartLVL15 is the strongest mass-produced LVL in the Australian for the same span properties as some common LVL sizes.



Short-term Water Repellent - H₂0 Shield™

SmartLVL 15 comes with a clear short-term water repellency. H₂0 Shield™ is a high penetrating water-based surface treatment, formulated to repel rain during storage and construction. H₂0 Shield™ is paintable with acrylic or oil based construction adhesives.



Treatment Options

All SmartLVL products come as H2S termite treated as standard, for protection south of the Tropic of Capricorn. H2 termite treatment for north of Tropic of Capricorn. H3 treatment against decay and termites.



Comprehensive Range

SmartLVL15 offers the most with SmartLVL 15 available in 42mm, 58mm and 75mm widths and a range of 15 different heights.



Sales 1800 33 77 03 Technical 1300 66 86 90 www.tilling.com.au





The information contained in this product document is current as at April 2022 and is based on data available to Tilling Timber Pty Ltd at the time of going to print. Tilling Timber Pty Ltd has used its reasonable endeavours to ensure the accuracy and reliability of the information contained in this document and, to the extent permitted by law, will not be liable for any inaccuracies, omissions or errors in this information nor for any actions taken in reliance on this information. Tilling Timber Pty Ltd reserves the right to change the information contained in this document without prior notice. It is important that you call the Tech Support customer Helpline on 1300 668 690 to confirm that you have the most up to date information available. © 2022 Tilling Timber Pty Ltd ABN 92 004 621 121 SmartFrame is a Registered Trademark of Tilling Timber